

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

10f45

PATENT NO. : 6,951,465 B2  
APPLICATION NO. : 10/603,047  
ISSUE DATE : Oct. 4, 2005  
INVENTOR(S) : SWEETLAND ET AL

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby

Corrected as shown below

THE TITLE PAGE SHOWING ILLUSTRATIVE FIGURE, SHOULD BE DELETED AND  
SUBSTITUTE THEREFORE THE ATTACHED TITLE PAGE

**DELETE** DRAWING SHEETS 1-40 AND **SUBSTITUTE** THEREFORE THE DRAWING  
SHEETS CONSISTING OF FIGS 1-41 AS SHOWN ON THE ATTACHED PAGE.



US006951465B2

20f45

(12) **United States Patent**  
Sweetland et al.

(10) Patent No.: **US 6,951,465 B2**  
(45) Date of Patent: **Oct. 4, 2005**

(54) **MULTIPLE-CONTACT WOVEN POWER CONNECTORS**

(75) Inventors: **Matthew Sweetland, Medford, MA (US); James Moran, Somerville, MA (US)**

(73) Assignee: **Tribotek, Inc., Burlington, MA (US)**

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

4,082,423 A	4/1978	Glista et al.	350/96.23
4,218,581 A	8/1980	Suzuki	174/117
4,462,657 A	7/1984	Snowdon et al.	339/256
4,508,401 A	4/1985	Casciotti et al.	339/14
4,639,054 A	1/1987	Kernsbergen	
4,651,163 A	3/1987	Sutera et al.	347/76
4,710,594 A	12/1987	Walling et al.	174/120
4,741,707 A	5/1988	Mondor	439/417
4,755,422 A	7/1988	Headrick et al.	442/7
4,778,950 A	10/1988	Lee et al.	174/356

(Continued)

#### FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **10/603,047**

(22) Filed: **Jun. 24, 2003**

(65) **Prior Publication Data**

US 2004/0005793 A1 Jan. 8, 2004

#### Related U.S. Application Data

(63) Continuation-in-part of application No. 10/375,481, filed on Feb. 27, 2003, which is a continuation-in-part of application No. 10/273,241, filed on Oct. 17, 2002.

(60) Provisional application No. 60/348,588, filed on Jan. 15, 2002.

(51) Int. Cl.<sup>7</sup> ..... **H01R 12/00**  
(52) U.S. Cl. .... **439/67; 439/329; 439/493**  
(58) Field of Search ..... **439/66-67, 91, 439/591, 482, 493, 329, 496, 930; 361/218; 174/117 M; 29/705**

(56) **References Cited**

#### U.S. PATENT DOCUMENTS

3,257,500 A	6/1966	Rusch et al.	174/116
3,495,025 A	2/1970	Ross	174/70
3,631,298 A	12/1971	Davis	317/101
3,639,978 A	2/1972	Schurman	29/628
3,654,381 A	4/1972	Copp	174/177
3,676,923 A	7/1972	Reimer	29/604
3,702,895 A	11/1972	De Sio	174/19
3,909,508 A	9/1975	Ross	174/117
3,927,284 A	12/1975	Anderson	200/5

EP	0512714	11/1992
EP	0901191	3/1999
EP	0932172	7/1999
JP	61185818	8/1986
JP	06176624	6/1994
JP	06251819	9/1994
JP	07037433	2/1995
JP	08106939	4/1996
WO	WO 95/08910	3/1995
WO	WO 01/75778	10/2001

*Primary Examiner*—Gary Paumen

*Assistant Examiner*—Edwin A. Leon

(74) *Attorney, Agent, or Firm*—Wilmer Cutler Pickering Hale and Dorr, LLP

(57) **ABSTRACT**

Multiple-contact woven power connectors are provided that have at least a first set of loading fibers and at least a first set of conductors. When woven onto a set of loading fibers, the conductors define a space. The loading fibers are capable of delivering contact forces at the contact points of the conductors. The conductors can include a power circuit or a return circuit. The power connectors may also include tensioning springs that are capable of generating tensile loads within the loading fibers. The power connectors may further include mating conductors that can be coupled to the power/return circuits. When disposed within the first and second spaces, respectively, electrical connections between the conductors and the mating conductors can be established.

**138 Claims, 40 Drawing Sheets**

